# **SPEC SHEETS**

# **MODEL: SSC-20-1S**

# **Vertical Reach In Refrigerator**

# **Product features**

- Digital Temperature Controller with automatic defrost function
- Includes three electrostatically painted shelves
- Corrosion Resistant stainless steel exterior and interior
- **©** Eco- Friendly R-290 Refrigerant
- Self Closing doors
- Door Locks
- Heavy duty Casters
- LED Lighting
- Safety and Sanitation Listed





### **Available Color**

Stainless steel

## **Accessories**

Steel Shelves

# **Product Highlights**



**Digital Temperature Controller** 



**Heavy Duty Casters** 



**Electrostatically painted Shelves** 

# **Certifications**





# Warranty

- 2 year parts and labor
- Additional 3 year compressor coverage


Residential: Assumes on liabillity for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.


# MODEL: SSC-20-1S





### **Plan view**







# **Technical data**

### **Dimensions**

| <b>External dimensions</b> | W:26 9/32 " D: 33 9/16" H:78 11/16" |
|----------------------------|-------------------------------------|
| Internal dimensions        | W: 22 15/64" D:26 5/8 " H:52 "      |
| Net volume                 | 16 ft3 453 L                        |
| Net weight                 | 281.5 lbs                           |
| Gross weight               | 308 lbs                             |
| Shelves Dimensions         | W: 21 7/16" D:23 5/16"              |
|                            |                                     |

#### **Performance data**

| Refrigerant charge | 2.3 oz             |
|--------------------|--------------------|
| Energy consumption | 1.59 kW/24Hrs      |
| Evaporator         | Forced ventilation |
| Expansion method   | Capillary          |
| Thawing method     | Natural            |
|                    |                    |
|                    |                    |

### Construction

| Exterior material | Stainless steel and Galvanized steel |
|-------------------|--------------------------------------|
| Interior material | Stainless steel                      |
| Number of shelves | 3                                    |
| Shelf material    | Electrostatically painted steel      |
| Door type         | Solid (Stainless steel)              |
| Door quantity     | 1                                    |

### **Electrical data**

| Power supply     | 115V/ 60 Hz          |
|------------------|----------------------|
| Amps             | 3 A                  |
| Length of cord   | 125 63/64 " (3200mm) |
| Lighting         | LED                  |
| Plug type        | NEMA 5-15P           |
| Controller       | Electric             |
| Compressor power | 1/5 HP / 395 W       |

## Cooling

| Equipment operating range    | 77 to 100.4 °F (25 to 38°C)     |
|------------------------------|---------------------------------|
| Controller temperature range | 35.1 to 46.2 °F (1.72 to 7.8°C) |
| Set Point                    | 36.3 °F (2.38°C)                |
| Cut In                       | 39.4 °F (4.11°C)                |
| Cut Out                      | 36.3 °F (2.38°C)                |
| Refrigerant                  | R290                            |
| Condenser                    | Wire and tube                   |

### Logistic data

| Trailer Loads              | 48 fit on a 53' trailer          |
|----------------------------|----------------------------------|
| Trailer Loads              | 42 fit on a 48' trailer          |
| Unit weight with packaging | 308 lbs                          |
| Dimensions with packaging  | W: 32 1/4" D: 37 3/4" H: 82 1/4" |
|                            |                                  |
|                            |                                  |